

Product	Tantalum chip capacitor	Series	TCT series P case
---------	-------------------------	--------	-------------------

Factory	ROHM APOLLO CO.,LTD.
	ROHM INTEGRATED SYSTEMS(THAILAND)CO.,LTD.

## 1. Test result

No.	Item	Test condition	Standard	n[pcs] Sample QTY.	Pn[pcs] NG QTY.															
1	Resistance to soldering heat	Dip in the solder bath. Solder temp. : 260±10°C Duration : 5±0.5s Repetition : 1time After the spesimens,leave it at room temperature for over 24h and then measure the sample.	As per 4.14 JIS C 5101-1 As per 4.6 JIS C 5101-3	22	0															
2	Temperature cycle	Repetition : 5cycles (1cycle : steps1~4) Without discontinuation. <table border="1" data-bbox="464 898 892 1068"> <thead> <tr> <th></th> <th>Temperature</th> <th>Time</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-55±3°C</td> <td>30±3min</td> </tr> <tr> <td>2</td> <td>Room temp.</td> <td>3min or less</td> </tr> <tr> <td>3</td> <td>125±2°C</td> <td>30±3min</td> </tr> <tr> <td>4</td> <td>Room temp.</td> <td>3min or less</td> </tr> </tbody> </table> After the spesimens,leave it at room temperature for over 24h and then measure the sample.		Temperature	Time	1	-55±3°C	30±3min	2	Room temp.	3min or less	3	125±2°C	30±3min	4	Room temp.	3min or less	As per 4.16 JIS C 5101-1 As per 4.10 JIS C 5101-3	22	0
	Temperature	Time																		
1	-55±3°C	30±3min																		
2	Room temp.	3min or less																		
3	125±2°C	30±3min																		
4	Room temp.	3min or less																		
3	Moisture resistance	After leaving the sample under such atmospheric condition that the temperature and humidity are 60±2°C and 90~95%(Relative Humidity) , respectively ,for 500±24h leave it at room temperature for over 24h and then measure the sample.	As per 4.22 JIS C 5101-1 As per 4.12 JIS C 5101-3	22	0															
4	Loading at high temperature	After applying the rated voltage for 1000+36/0h without discontinuation via the serial resistance of 3Ωor less at a temperature of 85±2°C , leave the sample at room temperature/ humidity for over 24h and measure the value.	As per 4.23 JIS C 5101-1 As per 4.15 JIS C 5101-3	22	0															

## 2.Failure criteria

No.	Test item	Performance	
1	Resistance to soldering heat	Appearance	There should be no significant abnormality.The indications should be clear.
		L.C.	Less than initial limit.
		$\Delta C/C$	Within $\pm 20\%$ of initial value
		$\tan\delta$	Less than 200% of initial limit.
2	Temperature cycle	Appearance	There should be no significant abnormality.The indications should be clear.
		L.C.	Less than 200% of initial limit.
		$\Delta C/C$	Within $\pm 20\%$ of initial value
		$\tan\delta$	Less than 200% of initial limit.
3	Moisture resistance	Appearance	There should be no significant abnormality.The indications should be clear.
		L.C.	Less than 200% of initial limit.
		$\Delta C/C$	Within $\pm 20\%$ of initial value
		$\tan\delta$	Less than 200% of initial limit.
4	Loading at high temperature	Appearance	There should be no significant abnormality.The indications should be clear.
		L.C.	Less than 200% of initial limit.
		$\Delta C/C$	Within $\pm 20\%$ of initial value
		$\tan\delta$	Less than 200% of initial limit.

## 3.Judgment

OK
----

## Notes

- 1) The information contained herein is subject to change without notice.
- 2) Before you use our Products, please contact our sales representative and verify the latest specifications :
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors.  
Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Products beyond the rating specified by ROHM.
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products are intended for use in general electronic equipment (i.e. AV/OA devices, communication, consumer systems, gaming/entertainment sets) as well as the applications indicated in this document.
- 7) The Products specified in this document are not designed to be radiation tolerant.
- 8) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, servers, solar cells, and power transmission systems.
- 9) Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 10) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 11) ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrant that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 12) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting from non-compliance with any applicable laws or regulations.
- 13) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 14) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations.  
More detail product informations and catalogs are available, please contact us.

## ROHM Customer Support System

<http://www.rohm.com/contact/>